

Slimline RSR



Advantages

- **Lightweight, compact ducted filter module for clean processes or medical suites**
- **Low pressure drop saves energy and low life-cycle cost reduces disposal costs**

Description: Fully welded ducted filter module for HEPA/ULPA filters. Available with bubble tight guillotine or radial bowtie damper.

Typical applications: Pharmaceutical and semiconductor manufacturing facilities, medical facilities and other clean process applications.

Efficiency: 95% at 0.3µ to 99.9995% at Most Penetrating Particle Size (MPPS).

Media: Microfine glass media, with continuous glass filament separators formed into a single mini-pleat filter pack.

Temperature: Maximum continuous operating temperature of 200° F (93° C).

Ratings: Tested in accordance with IEST Recommended Practice for Testing HEPA Filters; UL 900.

See Product Sheet 3422 for more details.

Model Number	Dimensions (inches)	Collar Diameter (inches)	Shipping Weight (lbs)
For 1-½" T-Bar Ceiling			
SL RSR, 23.62--23.62-10	23.62 x 23.62 x 5.37	10	34
SL RSR, 23.62-23.62-12	23.62 x 23.62 x 5.37	12	34
SL RSR, 23.62-35.62-10	23.62 x 35.62 x 5.37	10	40
SL RSR, 23.62-35.62-12	23.62 x 35.62 x 5.37	12	40
SL RSR, 23.62-41.62-10	23.62 x 41.62 x 5.37	10	46
SL RSR, 23.62-41.62-12	23.62 x 41.62 x 5.37	12	46
SL RSR, 23.62-47.62-10	23.62 x 47.62 x 5.37	10	50
SL RSR, 23.62-47.62-12	23.62 x 47.62 x 5.37	12	50
For 2" T-Bar Ceiling			
SL RSR, 23.12-23.12-10	23.12 x 23.12 x 5.37	10	34
SL RSR, 23.12-23.12-12	23.12 x 23.12 x 5.37	12	34
SL RSR, 23.12-35.12-10	23.12 x 35.12 x 5.37	10	40
SL RSR, 23.12-35.12-12	23.12 x 35.12 x 5.37	12	40
SL RSR, 23.12-41.12-10	23.12 x 41.12 x 5.37	10	46
SL RSR, 23.12-41.12-12	23.12 x 41.12 x 5.37	12	46
SL RSR, 23.12-47.12-10	23.12 x 47.12 x 5.37	10	50
SL RSR, 23.12-47.12-12	23.12 x 47.12 x 5.37	12	50

As part of our program for continuous improvement, Camfil reserves the right to change specifications without notice. 2013-08-20